



PRODUCT INFORMATION

Item Number	CPD
Product Colour	Grey/Black
Size Range	6-12
Primary Coating Polymer	Nitrile
Grip	Microfoam Nitrile
Cut Score	D
Heat Resistance	Contact Heat Level 1

FEATURES

Lining: 18 gauge seamless knitted liner is ultra-lightweight, breathable and highly flexible, ensuring ultimate comfort at all times

Comfort: Ultra-lightweight liner engineered without the addition of brittle glass fibre or steel; ensures the safety and superior comfort of the wearer during prolonged use

Unique Feature: Flat nitrile reinforcement between the thumb and forefinger offers additional protection in an area that is highly susceptible to wear and tear

Environmental: Each glove contains a minimum of 35% recycled material (rPET) showing our ongoing commitment to the planet

Heat Resistant: Achieves Level 1 for Contact Heat according to EN407. Can withstand temperatures of 100°C

Cut Resistant: Achieves cut level D according to EN388, for protection in high/very high risk cut hazard applications

Abrasion Resistant: Achieves a maximum score of Level 4 for abrasion resistance as defined by European Standard EN388

Grip: The palm coating is infused with microfoam bubbles increasing resistance to oils and maximising grip in wet and oily handling environments

Primary Coating Polymer: Nitrile

Fit: Soft seamless knitted liner provides superior comfort for this level of protection

Materials flex in conjunction with the hand's natural movement



FEATURES

Unique Feature: Tactile touchscreen compatible fingertips enable the wearer to use touch screen machinery or touch screen devices with precision and without the need to remove the glove

SECTORS

Automotive • Construction and Utility • Engineering and Manufacturing • Oil, Gas, and Renewables • Waste Management and Local Authority

STANDARDS

EN 388 Protective gloves against Mechanical Risks: 4X42D
 EN 407 Protective gloves against Thermal Risks (heat and/or fire): X1XXXX
 EN ISO 21420:2020 Protective gloves: General requirements



4X42D

X1XXXX

CAUTION

May contain latex in elasticated cuff which can cause allergic reactions, including anaphylactic response.

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555

STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. It is recommended to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear and tear.

PACKING

12 pairs per polybag
48 pairs per case
50 cases per pallet

DISPOSAL INSTRUCTIONS

Dispose of the product responsibly in accordance with local regulations.

Size	Outer Packaging Barcode
6	05010699857972
7	05010699858030
8	05010699858047
9	05010699858054
10	05010699858061
11	05010699858078
12	05010699858085

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555