



PRODUCT INFORMATION

Item Number	PHYC3
Product Colour	Orange/Black
Size Range	6-11
Primary Coating Polymer	Nitrile
Grip	Microfoam Nitrile
Cut Score	C

FEATURES

Lining: 18 gauge seamless knitted liner is ultra-lightweight, breathable and highly flexible, ensuring ultimate comfort at all times

Unique Feature: The Hydrophobic solution, which is applied through an intensive washing process, allows for a comprehensive and robust 3-Dimensional water resistant performance in wet and challenging conditions while maintaining maximum breathability

Silicone Free: The glove has been produced silicone free to eliminate silicone contamination whilst working in painting, bonding and product inspection processes within the engineering, manufacturing, and glass industries.

Cut Resistant: Achieves cut level C according to EN388, for protection in high risk cut hazard applications.

Mechanical Hazards Protection: Made from a technically engineered yarn, the liner attains excellent EN388 scores in all categories

Flexibility: Strategically designed to offer optimum levels of flexibility and comfort without compromising protection

Closure: Elasticated knitted wrist provides a secure fit and keeps hands free from dirt and debris

Abrasion Resistant: Achieves a maximum score of Level 4 for abrasion resistance as defined by European Standard EN388

Grip: The palm coating is infused with microfoam bubbles increasing resistance to oils and maximising grip in wet and oily handling environments

Primary Coating Polymer: Nitrile



FEATURES

Fit: Soft seamless knitted liner provides superior comfort for this level of protection
The glove has been designed to be tight fitting to give maximum dexterity in the most delicate of applications

Environmental: Gloves supplied in paper bands

SECTORS

Automotive • Construction and Utility • Engineering and Manufacturing • Oil, Gas, and Renewables • Waste Management and Local Authority

STANDARDS

EN 388 Protective gloves against Mechanical Risks: 4X43C
EN ISO 21420:2020 Protective gloves: General requirements



PPE CAT II



4X43C



CAUTION

May contain latex in elasticated cuff which can cause allergic reactions, including anaphylactic response.

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555

STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. It is recommended to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear and tear.

PACKING

10 pairs per paper band
60 pairs per case
50 cases per pallet

DISPOSAL INSTRUCTIONS

Dispose of the product responsibly in accordance with local regulations.

Size	Outer Packaging Barcode
6	05010699850331
7	05010699850348
8	05010699850355
9	05010699850362
10	05010699850379
11	05010699850386

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555